

18W内置升压单声道D类音频功放

18W Boosted Mono Class D Amplifier

■ FEATURES

- Spread spectrum technology
- Output Power
18W ($V_{BAT}=3.7V$, $R_L=4\Omega$, THD+N=10%, $f_{IN} = 1kHz$)
16W ($V_{BAT}=3.7V$, $R_L=4\Omega$, THD+N=1%, $f_{IN} = 1kHz$)
8W ($V_{BAT}=3.3V$, $R_L=8\Omega$, THD+N=1%, $f_{IN} = 1kHz$)
- Power Supply V_{BAT} : 3.0V~12V
- High Efficiency Class H Boost Converter
 - Multiple boost voltages automatically adjust Class D audio amplifier
 - Extends the playing time in battery supply applications
 - Adjustable switch peak current limit to avoid over-pulling on battery current
- Over Current Protection, Thermal Protection, over voltage protection function included
- Pb-Free Packages, ETSSOP20
- 扩频技术
- 输出功率
18W ($V_{BAT}=3.7V$, $R_L=4\Omega$, THD+N=10%, $f_{IN} = 1kHz$)
16W ($V_{BAT}=3.7V$, $R_L=4\Omega$, THD+N=1%, $f_{IN} = 1kHz$)
8W ($V_{BAT}=3.3V$, $R_L=8\Omega$, THD+N=1%, $f_{IN} = 1kHz$)
- V_{BAT} 供电范围: 3.0V至12V
- 高效H类升压功能
- 自适应功放功率的升压轨, 延长电池播放时间
- 可调节最大限流值, 有效防止电池拉死
- 保护功能:过流/过热/过压保护功能
- 无铅封装, ETSSOP20

■ APPLICATIONS

- Bluetooth/Wi-Fi Speakers
- Portable Speakers
- 蓝牙/ Wi-Fi音箱
- 便携式音箱
- Smart speakers
- Smart Home
- 智能音箱
- 智能家居

■ DESCRIPTION

HTA8111, integrated with a boost converter, is a mono Class D audio amplifier that drives up to continuous 18W (10% THD+N, 1kHz) into 4ohm speaker from a Li-battery voltage.

HTA8111 integrates an adaptive boost converter that generates a Class D amplifier supply rail tracking the audio signal, which will significantly improve the efficiency and extends the playing time in battery supply applications. Configurable current limit is adopted to avoid accidental large peak current.

HTA8111 integrates Spread Spectrum Control technology to achieve advanced EMI suppression. The Gain of HTA8111 is 32dB.

As for protection function, over current protection function for speaker output terminals, over temperature protection function and over voltage protection for boost converter output are also prepared.


HTA8111是一款内置升压的单声道D类音频功率放大器，由锂电池供电时，THD+N=10%，能连续输出18W功率（4Ω负载）。

HTA8111内置可动态调节的升压，可以提供一个适应不同输出功率的电压给D类功放，其可大幅提高系统效率，延长电池续航时间。HTA8111可配置升压限流值，以防止过大的电流尖峰。

HTA8111具有先进的扩频功能来抑制EMI。HTA8111的增益为32dB。



此外，HTA8111集成了输出端过流保护、片内过温保护、升压过压保护等功能。

TYPICAL APPLICATION



ORDERING INFORMATION

Part Number	Package Type	Marking	Operating Temperature Range	Shipping Package / MOQ
HTA8111MTER	ETSSOP20 (MTE)	HTA8111 YYYMAAB ¹	-40℃~85℃	Tape and Reel (R) / 3000pcs

Part Number

Production Tracking Code


IMPORTANT NOTICE**注意**

Heroic Electronic Technology (Jiaxing) Co., Ltd (HT) reserves the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any products or services. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

禾润电子科技（嘉兴）股份有限公司（以下简称HT）保留对产品、服务、文档的任何修改、更正、提高、改善和其他改变，或停止提供任何产品和服务的权利。客户在下单和生产前应确保所得到的信息是最新、最完整的。

HT assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using HT components.

HT对相关应用的说明和协助以及客户产品的板级设计不承担任何责任。

HT products are not authorized for use in safety-critical applications (such as life support devices or systems) where a failure of the HT product would reasonably be expected to affect the safety or effectiveness of that devices or systems.

HT的产品并未授权用于诸如生命维持设备等安全性极高的应用中。

The information included herein is believed to be accurate and reliable. However, HT assumes no responsibility for its use; nor for any infringement of patents or other rights of third parties which may result from its use.

本文中的相关信息是精确和可靠的，但HT并不对其负责，也不对任何可能的专利和第三方权利的侵害负责。

Following are URLs and contacts where you can obtain information or supports on any HT products and application solutions:

下面是可以联系到我公司的相关链接和联系方式：

禾润电子科技（嘉兴）股份有限公司
Heroic Electronic Technology (Jiaxing) Co., Ltd.

地址：浙江省嘉兴市南湖区亚太路906号科创CBD园区21号楼11层

Add: 11th floor, Building 21, No. 906, Yatai Road, Jiaxing, Zhejiang Province

Sales: 0573-82586608, sales@heroic.com.cn

Support: 0573-82586151, support@heroic.com.cn

Website: www.heroic.com.cn; wap.heroic.com.cn

Wechat MP: HEROIC_JX

请及时关注禾润官方微信公众号，随时获取最新产品信息和技术资料！

